



BY616



FEATURES

- ▶ High drainage and wet-slip resistance
- ▶ Low rolling resistance
- ▶ Less non-scale wear

SIZE	PR	LOAD INDEX	MAX/LOAD (Kg)	BRITISH SYSTEM MAX/LOAD (Kg)	PRESSURE (Kpa)	BRITISH SYSTEM PRESSURE (PSI)	SPEED RATE	TREAD DEPTH (mm)	STANDARD RIM	ALTERNATIVE RIM
215/75R17.5	16	127/124	1750/1600	3860/3525	830	120	M	13.5	6.00	6.75
235/75R17.5	16	132/129	2000/1850	4410/4080	830	120	M	13.5	6.75	7.50



BY996



FEATURES

- ▶ Powerful driving force
- ▶ Stone-proof
- ▶ Low noise
- ▶ Long life-time

SIZE	PR	LOAD INDEX	MAX/LOAD (Kg)	BRITISH SYSTEM MAX/LOAD (Kg)	PRESSURE (Kpa)	BRITISH SYSTEM PRESSURE (PSI)	SPEED RATE	TREAD DEPTH (mm)	STANDARD RIM	ALTERNATIVE RIM
215/75R17.5	16	127/124	1750/1600	3860/3525	830	120	M	15.5	6.00	6.75
235/75R17.5	16	132/129	2000/1850	4410/4080	830	120	M	15.5	6.75	7.50

